

# TECHNICAL DATA SHEET

## Fischer-Tropsch Wax ANW-5801

Neutral draft for commercial and technical evaluation

<b>Product code</b>	ANW-5801	<b>Chemical family</b>	Synthetic paraffin wax / Fischer-Tropsch wax
<b>CAS / EC No.</b>	8002-74-2 / 232-315-6	<b>Product form</b>	Pellet

### Product description

ANW-5801 is a higher-congealing Fischer-Tropsch wax supplied in pellet form. It is intended for industrial wax applications that require higher hardness, low oil content, and good handling in pellet form. Typical reference end uses include container candles, pillar candles, moisture-resistant board wax systems, dipping wax for corrugated cartons, hot-melt adhesives, and ceramic wax applications.

### Typical technical data

Note: Values above are commercial reference data for grade description. Final released batch values should be confirmed by the lot-specific Certificate of Analysis (COA).

Property	Unit	Test method	Reference value
<b>Congealing point</b>	°C	ASTM D938 / GB/T 28724-2022	<b>58-60</b>
<b>Penetration (100 g, 25°C, 1/10 mm)</b>	1/10 mm	ASTM D1321 / GB/T 4985-2021	<b>≤18</b>
<b>Odor</b>	-	ASTM D1833 / SH/T 0414-2004	<b>≤1</b>
<b>Oil content</b>	wt%	ASTM D721 / GB/T 3554-2008	<b>≤0.75</b>
<b>Color, Saybolt</b>	-	ASTM D156 / GB/T 3555-2022	<b>≥27</b>
<b>Kinematic viscosity at 100°C</b>	mm <sup>2</sup> /s	ASTM D445 / GB/T 265-88	<b>Report on COA</b>

<b>Physical form</b>	-	Visual	<b>Pellet</b>
<b>Standard packing</b>	-	-	<b>25 kg bag</b>

<p><b>Key product features</b></p> <ul style="list-style-type: none"> <li>• Higher congealing grade with harder wax profile</li> <li>• Low oil content for cleaner industrial formulations</li> <li>• Pellet form for easier dosing and melting operations</li> <li>• Suitable as a performance wax where additional hardness is needed</li> </ul>	<p><b>Typical applications</b></p> <ul style="list-style-type: none"> <li>• Container candles</li> <li>• Pillar candles</li> <li>• Moisture-resistant board wax systems</li> <li>• Dipping wax for corrugated cartons</li> <li>• Hot-melt adhesives</li> <li>• Ceramic wax</li> </ul>
--	---

## Storage and handling guidance

- Store in a clean, dry, well-ventilated area away from direct heat, ignition sources, and strong oxidizing agents.
- Keep containers or bags closed when not in use to avoid contamination.
- If handled in molten form, avoid unnecessary overheating. For safe melting, personal protection, first-aid, and emergency measures, review the latest Safety Data Sheet (SDS).

### Commercial / compliance note

- This document is a Technical Data Sheet and does not replace the Safety Data Sheet (SDS).
- Typical applications stated in this sheet are reference uses only and do not constitute a representation of regulatory approval or suitability in the customer's specific formulation, process, or jurisdiction.
- For EU, UK, or other regulated markets, product classification, label language, SDS supply, and registration or importer coverage must be confirmed for the actual legal entity and destination market before shipment.
- For personal care, pharmaceutical, food-contact, chewing-gum, or other regulated end uses, separate grade-specific compliance review and supporting documentation are required before commercial supply.

Disclaimer: The information in this sheet is intended to describe typical technical characteristics for product evaluation and commercial discussion. It should not be treated as a binding warranty or a substitute for customer qualification testing, SDS review, or contractual specification unless expressly agreed in writing.